













The SeceuroGuard retractable gate system combines a classic appearance with effective protection, ideal for the home or workplace. The high security 1001 is tested and approved to LPS 1175. The system can be easily fitted to the face or reveal of a window or door aperture and can be specified in a single or double-sash configuration. Where a clear walk through is required SeceuroGuard's bottom track can, as an optional extra, be made to fold up.

- **Versatile** Fits internally in either the window reveal or around the opening in either single or double-sash configuration
- Ease of use Smooth top running operation with an optional extra of a fold up bottom track to leave doorways unobstructed
- Secure Multi-point locking operating from a single key
- **High quality finish** Supplied in high quality white powder coated finish as standard

Optional RAL colours available on this and many of our security products:



Product Matrix

SeceuroShield Physical Security	Page	Investment & Security	Domestic	Retail	Commercial	Bar / Servery / Kiosk / Cabinet	Maximum & Minimum Widths
SeceuroShield 3801 Insurance Approved Security Shutters		E E E	•	•	•	•	Min: 900 mm Max: 3000 x 4000 mm
SeceuroShield 38 Built-On & Built-On Security Shutters Solid Slats		E E E E	•	•	•	•	Min: 500 mm Max: 4000 x 5000 mm
SeceuroShield 75 Built-On Security Shutters Solid Slats		E E E E		•	•	•	Min: 1000 mm Max: 6000 x 3400 mm
SeceuroShield 60 Built-On & Built-On Security Shutters Solid Slats		E E E E		•	•	•	Min: 900 mm Max: 6000 x 5000 mm
SeceuroShield 150 Built-On & Built-On Security Shutters Solid Slats		E E E	•			•	Min: 500 mm Max: 3400 x 4000 mm
SeceuroShield 77 Built-On Security Shutters Solid Slats		E E E E	•	•	•	•	Min: 900 mm Max: 5400 x 4000 mm
SeceuroVision 900 See-Through Shutters 55-69% Vision		E E E		•	•	•	Min: 900 mm Max: 5000 x 4000 mm
SeceuroVision 800 See-Through Shutters Punched & Glazed 62% Vision		E E E		•	•	•	Min: 900 mm Max: 6000 x 5000 mm
SeceuroVision 75 See-Through Shutters Perforated 25% Vision		E E E E		•	•	•	Min: 1000 mm Max: 6000 x 3400 mm
SeceuroVision 38 See-Through Shutters Punched & Glazed 45% Vision		E E E E	•	•	•	•	Min: 500 mm Max: 3000 x 5000 mm
SeceuroVision 38 See-Through Shutters Perforated 17% Vision		E E E E	•	•	•	•	Min: 500 mm Max: 3000 x 5000 mm
SeceuroGuard 1000 Retractable Security Gates		E E E	•	•	•	•	Min: 500 x 500 mm Max: 6000 x 3500 mm
SeceuroGuard 1001 Insurance Approved Retractable Security Gates		EEE	•	•	•	•	Min: 500 x 1000 mm Max: 6000 x 3000 mm
SeceuroBar Removable Window Bars		E E E	•	•	•	•	Min: 250 x 200 mm Max: 3000 x 2100 mm
Xpanda Deterrant Security Products		E E E O O O		•	•	•	Min: 900 x 850 mm Max: 1800 x 2500 mm Max: 1800 x 2500 mm

- 1 Sizes quoted may not be available with some operation modes and may alter depending on product application, wind loading or whether installed as a secondary or sole closure. Limitations apply to maximum overall sizes.
- 2 Please note the maximum sizes quoted for SeceuroShield 75 and SeceuroVision 75 are applicable to the continental style shutter with aluminium head box and guide rails. These products are also available with traditional galvanised steel channels and head box. The maximum sizes for the traditional style are: maximum width 6400 mm, maximum height 4700 mm and maximum area 20 sqm.

Insulated	Secured By Design	LPCB Insurance Approved	Electric (E) or Manual (M)	Standard Finishes	Any RAL/BS Colour as an Extra
	√	✓	Е	3	✓
			E & M	3	✓
			E & M	1	✓
			E & M	3	✓
1			E & M	4	
1			E & M	12	
			E & M	1	✓
			E & M	3	√
			E & M	1	✓
			E & M	3	✓
			E & M	4	✓
			М	27	✓
	J	1	М	27	√
			М	1	√
			М	1	

Secured by Design



Secured by Design is the official UK Police flagship initiative supporting the principles of 'designing out crime' by use of effective crime prevention and security standards for a wide range of products and applications.

Only products which have been tested and meet the required technical standard can be awarded the Police Preferred Specification.

For more information on this initiative refer to:

www.securedbydesign.com

Insurance approved security



The rigorous LPS 1175 burglary resistance standard is operated by the Loss Prevention Certification Board (LPCB). LPCB are the UK's leading independent certification body and the LPS 1175 standard is recognised and endorsed by 16 organisations including the Association of British Insurers and the Association of Chief Police Officers.

For more information on the scheme refer to:

www.brecertification.co.uk